

Scilab Manual for
Applied Mathematics for Communication
Engineers
by Prof Prarthan Mehta
Others
Dharmsinh Desai University¹

Solutions provided by
Prof PRARTHAN MEHTA
Others
DHARMSINH DESAI UNIVERSITY

May 18, 2024

¹Funded by a grant from the National Mission on Education through ICT,
<http://spoken-tutorial.org/NMEICT-Intro>. This Scilab Manual and Scilab codes
written in it can be downloaded from the "Migrated Labs" section at the website
<http://scilab.in>

Contents

List of Scilab Solutions	3
1 TRUNCATION OF A SQUARE WAVE USING FOURIER SERIES EXPANTION	4
2 ESTIMATION OF THE ROOTS(ZEROS) FOR A REAL VALUED FUNCTION USING NEWTON-RAPHSON METHOD	8
3 DFT & IDFT OF A GIVEN SEQUENCE	11
4 SYSTEM RESPONSE USING CONVOLUTION	14
5 NODE VOLTAGE & MESH CURRENT ANALYSIS	15
6 STABILITY OF A FEEDBACK SYSTEM IN XCOS	18
7 IMPLEMENTATION OF CHANNEL CODING-LINEAR BLOCK CODE	19
8 FILTER DESIGN USING LAPLACE TRANSFORM	24
9 SIGNAL MODULATION	26
10 APPLICATION OF LINEAR ALGEBRA IN DIGITAL COM- MUNICATION	28

List of Experiments

Solution 1.1	Truncation of the Square Wave	4
Solution 2.1	Estimation or Roots	8
Solution 3.1	DFT of a Given Sequence	11
Solution 3.2	IDFT of the given response	12
Solution 4.1	System Response using Convolution	14
Solution 5.1	Node Voltage	15
Solution 5.2	Mesh Current	16
Solution 7.1	Linear Block Coder Decoder	19
Solution 8.1	Filter Design	24
Solution 9.1	BPSK	26
Solution 10.1	Rotation of a Vector	28

Experiment: 1

TRUNCATION OF A SQUARE WAVE USING FOURIER SERIES EXPANTION

Scilab code Solution 1.1 Truncation of the Square Wave

```
1 v=1;  
    // Multiplier Voltage  
2 w=15;  
  
    // Frequency  
3 t=0:0.001:0.99;  
  
    // Incremental Time Stamp  
4 x1=v*(cos(w*t)-cos(3*w*t)/3)/%pi;  
    //  
    First 2 Components of the Fourier Series of a  
    Square Wave with Frequency W rad/sec  
5 x2=v*(cos(w*t)-cos(3*w*t)/3+cos(5*w*t)/5)/%pi;  
    // First 3
```

```

Components of the Fourier Series of a Square Wave
with Frequency W rad/sec
6 x3=v*(cos(w*t)-cos(3*w*t)/3+cos(5*w*t)/5-cos(7*w*t)
/7)/%pi; //First 4 Components
    of the Fourier Series of a Square Wave with
Frequency W rad/sec
7 x4=v*(cos(w*t)-cos(3*w*t)/3+cos(5*w*t)/5-cos(7*w*t)
/7+cos(9*w*t)/9)/%pi; //First 5 Components
    of the Fourier Series of a Square Wave with
Frequency W rad/sec
8 x5=v*(cos(w*t)-cos(3*w*t)/3+cos(5*w*t)/5-cos(7*w*t)
/7+cos(9*w*t)/9-cos(11*w*t)/11)/%pi; ///
    First 6 Components of the Fourier Series of a
Square Wave with Frequency W rad/sec
9 x6=v*(cos(w*t)-cos(3*w*t)/3+cos(5*w*t)/5-cos(7*w*t)
/7+cos(9*w*t)/9-cos(11*w*t)/11+cos(13*w*t)/13)/
%pi; //First 7 Components of the Fourier
    Series of a Square Wave
10 subplot(3,2,1)

    //Deviding the Figure Qindow in Six Subwindows to
    plot diffenrent components
11 plot(x1);

    //Plotting the First 2 components of the Fourier
    Series of a Square Wave
12 title('Square Wave Contructed with First 2
    Components of Fourier Series'); //Assigning
    a Title of the Figure
13 xlabel('Samples');

    //Assigning an X-label of the figure
14 ylabel('Amplitude (V)');

    //Assigning of a Y-label of the figure
15 subplot(3,2,2)
16 plot(x2);

```

```

    // Plotting the First 3 components of the Fourier
    Series of a Square Wave
17 title('Square Wave Constructed with First 3
    Components of Fourier Series');           // Assigning
    a Title of the Figure
18 xlabel('Samples');

    // Assigning an X-label of the figure
19 ylabel('Amplitude (V)');

    // Assigning of a Y-label of the figure
20 subplot(3,2,3)
21 plot(x3);

    // Plotting the First 4 components of the Fourier
    Series of a Square Wave
22 title('Square Wave Constructed with First 4
    Components of Fourier Series');           // Assigning
    a Title of the Figure
23 xlabel('Samples');

    // Assigning an X-label of the figure
24 ylabel('Amplitude (V)');

    // Assigning of a Y-label of the figure
25 subplot(3,2,4)
26 plot(x4);

    // Plotting the First 5 components of the Fourier
    Series of a Square Wave
27 title('Square Wave Constructed with First 5
    Components of Fourier Series');           // Assigning
    a Title of the Figure
28 xlabel('Samples');

    // Assigning an X-label of the figure
29 ylabel('Amplitude (V)');

```

```

        // Assigning of a Y-label of the figure
30
31 subplot(3,2,5)
32 plot(x5);

        // Plotting the First 6 components of the Fourier
        Series of a Square Wave
33 title('Square Wave Constructed with First 6
Components of Fourier Series');           // Assigning
a Title of the Figure
34 xlabel('Samples');

        // Assigning an X-label of the figure
35 ylabel('Amplitude (V)');

        // Assigning of a Y-label of the figure
36
37 subplot(3,2,6)
38 plot(x6);

        // Plotting the First 7 components of the Fourier
        Series of a Square Wave
39 title('Square Wave Constructed with First 7
Components of Fourier Series');           // Assigning
a Title of the Figure
40 xlabel('Samples');

        // Assigning an X-label of the figure
41 ylabel('Amplitude (V)');

        // Assigning of a Y-label of the figure
42
43
44 //----Input Parameters---//
45 //v==> voltage
46 //w==>Frequency

```

Experiment: 2

ESTIMATION OF THE ROOTS(ZEROS) FOR A REAL VALUED FUNCTION USING NEWTON-RAPHSON METHOD

Scilab code Solution 2.1 Estimation or Roots

```
1
2
3 clear
4
5
6 function [y, deriv] = fcn_nr(x)
7     y = x^3 + 4*(x)^2 -10;
8     deriv = 3*(x)^2 + 8*x;
9
10 endfunction
11
12 xp = -15:1:15;
13 n = length(xp);
```

```

14 for i=1:n
15     yp(i) = fcn_nr(xp(i));
16 end
17 plot(xp,yp)
18 xlabel('x')
19 ylabel('y')
20 title('Plot of function')
21
22
23
24 x = input('Enter initial guess of root location: ');
25
26 itermax = 10;          // % max # of iterations
27 iter = 0;
28 errmax = 0.00001;      // % convergence tolerance
29 error1 = 1;
30
31
32 while error1 > errmax & iter < itermax
33
34     iter = iter + 1;
35     [f fprime] = fcn_nr(x);
36     if fprime == 0
37         break;
38     end;
39
40     xnew = x - f / fprime;
41
42     error1 = abs((xnew - x)/xnew) * 100; // % find
43                                         change from previous
44
45     x = xnew          // % set up for next iteration
46     disp('Iteration No.')
47     disp(iter)
48     disp('the estimated value of the variable x is=')
49     disp(x)
50

```

```
51 end
52
53 //----Input Parameters----//
54
55 //This code will work for different functions of the
      variable x. hence the user has to modify the
      function & its derivative accordingly
56 //Itermax==>maximum number of iteration for which
      the method has to estimate the value of the
      variable
57 //errmax==>maximum tolerable error
```

Experiment: 3

DFT & IDFT OF A GIVEN SEQUENCE

Scilab code Solution 3.1 DFT of a Given Sequence

```
1 clear
2 clc
3
4 x=input('enter the digital sequence'); // Input
      the digital sequence
5 N=length(x);

      // Finding the length of the sequence for N-point
      DFT
6
7 for k=1:N
8     y(k)=0;
9     for n=1:N
10        y(k)=y(k)+(x(n)*(exp(-%i*2*pi*(k-1)*(n-1)/N
11           ))); // Equation to
              find DFT
12    end
13 end
```

```

13 disp('The DFT of the given sequence is:')
// Displaying the DFT
14 disp(y)
15
16
17 //---Input Parameters---//
18
19 //x==>digital sequence for which DFT has to be found

```

Scilab code Solution 3.2 IDFT of the given response

```

1 clear
2 clc
3
4 x=input('Enter the sequence:');
//Input the DFT
5 N=length(x);

//Finding the length to get N-point IDFT
6 for n=1:N
7     y(n)=0;
8     for k=1:N
9         y(n)=y(n)+(x(k)*(exp(%i*2*pi*(k-1)*(n-1)/N))
10            ));                                //Equation to
11            find the IDFT
12    end
13    y(n)=y(n)/N;
14 end
13 disp('The IDFT of the given sequence is:')
//Displaying
14 disp(y)
15

```

```
16
17 //—Input Parameters---//  
18
19 //x==>Frequency domain digital representation of the  
sequence (DFT) for which IDFT has to be found
```

Experiment: 4

SYSTEM RESPONSE USING CONVOLUTION

Scilab code Solution 4.1 System Response using Convolution

```
1
2 X=input('Enter the Input data Sequence X[n]: ');
3 H=input('Enter the Response of the System H[n]: ');
4
5 Y=conv(X,H);
6
7 disp('The response of the given system for the given
      input data sequence is Y[n]: ');
8 disp(Y);
9
10
11 //——Input Variables --//  

12 //X==>digital sequence X[n]  

13 //H==>filter impulse response H[n]
```

Experiment: 5

NODE VOLTAGE & MESH CURRENT ANALYSIS

Scilab code Solution 5.1 Node Voltage

```
1 //number of loops in the networks=2
2
3 v1=input('Enter the voltage in loop-1 (in V):');
4 i2=input('Enter the current through loop-2 (in A):')
5 ;
6 r2=input('Enter the resistance in series with V1 in
loop-1 (in Ohm):');
7 r1=input('Enter the resistance between v2 & GND. (a
common element bwetween loop-1 & 2) (in Ohm):');
8
9 //Teh node voltage at node-2 can be solved as
10 //temp1=(v2-v1)/r2;
11 //temp2=(v2/r1)'
12 //0=temp1+temp2+i2;
13 temp3=i2*r1*r2;
14 temp4=v1/r2;
15 temp5=temp4-temp3;
16 temp6=temp5*r1*r2;
17 v2=temp6/(r1+r2);
```

```

17
18 disp('Voltage at Node-2 V2=');
19 disp(v2)
20
21
22 //---Input Variables---//
23
24 //v1==>equivalent voltage in loop 1 --constant
25 //i2==>value of the current source in lloop 2--constant
26 //r2==>value of the resistance in series with V1 in loop 1-- constant
27 //r1==>value of the resistance in the common branch in loop 1 & loop 2--constant

```

Scilab code Solution 5.2 Mesh Current

```

1 //number of loops in the networks=2
2
3 v1=input('Enter the voltage in loop-1 (in V):');
4 v2=input('Enter the voltage in loop-2 (in V):');
5 r1=input('Enter the resistance in series with V1 in loop-1 (in Ohm):');
6 r2=input('Enter the resistance between v2 & GND. (a common element bwetween loop-1 & 2) (in Ohm):');
7 r3=input('Enter the resistance in series with V2 in loop-2 (in Ohm):');
8
9 //The mesh current can be solved as
10 //v1=(r1+r2)*i1-r2*i2;
11 //v2=-r2*i1+(r2+r3)*i2;
12
13 // [v]=[r][i];
14
15 // [i]=[v][R]; where [R]=inv([r]);

```

```

16
17
18 v=[v1;v2];
19
20 r=[r1+r2 -r2 ; -r2 r2+r3];
21
22 // i=[i1;i2];
23
24 R=inv(r);
25
26
27 i=R*v;
28
29 disp('the current through the loops=')
30 disp(i)
31
32
33 //—Input variables--//
34 //v1==>voltage in loop 1—constant
35 //v2==>voltage in loop 2—constant
36 //r1==>resitance in loop 1 — constant
37 //r2==>resitance in the common branch of loop1 &
    loop 2 —constant
38 //r3==>resitance in loop 2 — constant

```

Experiment: 6

STABILITY OF A FEEDBACK SYSTEM IN XCOS

This code can be downloaded from the website www.scilab.in This code

can be downloaded from the website www.scilab.in

Experiment: 7

IMPLEMENTATION OF CHANNEL CODING-LINEAR BLOCK CODE

Scilab code Solution 7.1 Linear Block Coder Decoder

```
1
2
3 //%% this is a linear block code main script file%
4 clear
5
6 global P n k;
7
8 n=7;
9 k=4;
10 P=[1 1 0; 0 1 1; 1 0 1;1 1 1]; //%% parity matrix of
    size k*(n-k) to be
11 // % selected so that
    the systematic generator
12 // % matrix is
    linearly independent or full rank
13 // % matrix
14
```

```

15 //%(n,k) linear block code where k = no. of input
   data bits and n= no. of o/p
16 //% data bits. code rate=k/n
17 //% x is an input vector containing k bits
18
19 //%This is an linear block encoding function file%
20 function y1=linblkcode(x);
21 global P n k;
22 n=7;
23 k=4;
24 P=[1 1 0; 0 1 1; 1 0 1;1 1 1];
25 //x=[0 1 1 0];
26
27 //G=[ ] ; // % Generator matrix k*n
28 G=[eye(k,k) P];
29
30 y1=zeros(1,n);
31 for i=1:k
32     var(i,:)=x(1,i) & G(i,:);
33     var(i,:)=bool2s(var(i,:));
34     y1(1,:)=bitxor(var(i,:),y1(1,:));
35 end
36
37 endfunction
38
39
40 //%This is a linear block syndrome decoding function
   file%
41
42 function x1=linblkdecoder(y)
43 //% here y is received vector 7 bits long
44
45 //%(7,4) linear block code
46 global P n k;
47
48
49 //H=[ ] ; //% PARITY CHECK MATRIX
50

```

```

51 H=[P' eye((n-k),(n-k))];
52 Ht=H'; // transpose of H
53
54 S=zeros(1,n-k); // syndrome of received vector x
55 for i=1:n-k
56     S(i)=y(1) & Ht(1,i);
57     S(i)=bool2s(S(i));
58     for j=2:n
59
60         S(i)=bitxor(S(i), bool2s((y(j) & Ht(j,i))));
61     end
62 end
63
64
65
66 // %*****SYNDROME LOOK UP TABLE*****
67
68 // %*****SYNDROME LOOK UP TABLE*****
69 //%
70 if S==[0 0 0]
71     e=[0 0 0 0 0 0];
72     z=bitxor(y,e);
73 end
74
75 if S==[0 0 1]
76     e=[0 0 0 0 0 0 1];
77     z=bitxor(y,e);
78 end
79 if S==[0 1 0]
80     e=[0 0 0 0 0 1 0];
81     z=bitxor(y,e);
82 end
83 if S==[1 0 0]
84     e=[0 0 0 0 1 0 0];
85     z=bitxor(y,e);
86 end
87 if S==[1 1 1]
88     e=[0 0 0 1 0 0 0];

```

```

89      z=bitxor(y,e);
90  end
91 if S==[1 0 1]
92   e=[0 0 1 0 0 0 0];
93   z=bitxor(y,e);
94 end
95 if S==[0 1 1]
96   e=[0 1 0 0 0 0 0];
97   z=bitxor(y,e);
98 end
99 if S==[1 1 0]
100   e=[1 0 0 0 0 0 0];
101   z=bitxor(y,e);
102 end
103
104
105
106
107 x1=z(1,1:k);
108 endfunction
109
110
111 x=[0 1 1 0]; // % input bits to the
112 // encoder of size 1* k
113 y1=linblkcode(x); // // % y1 is the
114 // output of linear block encoder
115
116 e1=[1 0 0 0 0 0 0]; // % intentionally
117 // error introduced after
118 // % encoding and
119 // before sending to decoder (in
120 // % this case pls
121 // introduce only one bit error)
122 y=bitxor(y1,e1); // % input that will
123 // be made available to linear
124 // % block decoder
125
126
127
128
129
130

```

```

121 x1=linblkdecoder(y) // % x1 is the output
    of the linear block decoder
122 // % which will be
    same as x provided that
    here
123 // % have introduced
    only one bit error
124
125 disp('The information signal=')
126 disp(x)
127 disp('The transmitted encoded signal=')
128 disp(y1)
129 disp('The received signal=')
130 disp(y)
131 disp('The denoised signal=')
132 disp(x1)
133
134
135 //—Input variables —//
```

136

137 // (n,k)==>constants according to the design of
linear block code

138 //P==>parity matrix of size k*(n-k) to be selected
so that the systematic generator matrix is
linearly independent or full rank matrix

139 //x==>information signal—vector

Experiment: 8

FILTER DESIGN USING LAPLACE TRANSFORM

Scilab code Solution 8.1 Filter Design

```
1
2
3
4
5 x=input('Enter the input data sequence');
6 b=input('Enter the co-effitients for the numerator
polynomial:');
7 a=input('Enter the co-effitients for the denominator
polynomial:');
8
9 y=filter(b,a,x);
10
11
12 disp('The input signal is=')
13 disp(x)
14 disp('The filtered signal is=')
15 disp(y)
16 //—Input Variables --//
```

```
18 //x==>input digital sequence—vector  
19 //b==>vecotr  
20 //a==>vector
```

Experiment: 9

SIGNAL MODULATION

Scilab code Solution 9.1 BPSK

```
1 function out_a=BPSK_a(bit,no_shift,shift)
2 if bit == 1
3     out_a = no_shift
4 else
5     out_a = shift
6 end
7
8 endfunction
9
10 t=0:0.001:1;
11 bit_1=0;
12
13 no_shift1=sin(2*pi*10*t);
14 shift1=sin(2*pi*10*t+(%pi));
15
16
17
18 out=BPSK_a(bit_1,no_shift1,shift1);
19 plot(t,out)
20
21 t1=1:0.001:2;
```

```
22 bit_2=1;
23
24 out1=BPSK_a(bit_2,no_shift1,shift1)      ;
25 plot(t1,out1)
26
27 xlabel('time')
28 ylabel('Amplitude')
29 //—Input Variables
30 //bit_1 & bit_2==> digital logic 1 or 0
```

Experiment: 10

APPLICATION OF LINEAR ALGEBRA IN DIGITAL COMMUNICATION

Scilab code Solution 10.1 Rotation of a Vector

```
1 r1=[1 0];
2 r2=[0 1];
3 theta=input("Enter the theta (angle for rotation in
radian):")
4 rotat=[cos(theta) sin(theta); -sin(theta) cos(theta)
];
5
6 R=[r1 ; r2];
7
8 new_R=R*rotat;
9
10 rotated_r1=new_R(1,:);
11 rotated_r2=new_R(2,:);
12
13 disp('The vector r1=')
14 disp(r1)
15 disp('The rotated vector r1=')
```

```
16 disp(rotated_r1)
17
18 disp('The vector r2=')
19 disp(r2)
20
21 disp('The rotated vector r2=')
22 disp(rotated_r2)
23
24
25 //—Input variables --//
```

```
26
27 //thera==>constant
```