

Scilab Manual for
Advanced Mathematical Physics-I
by Dr Triranjita Srivastava
Physics
Kalindi College, University Of Delhi¹

Solutions provided by
Dr Triranjita Srivastava
Physics
Kalindi College, University Of Delhi

May 19, 2024

¹Funded by a grant from the National Mission on Education through ICT,
<http://spoken-tutorial.org/NMEICT-Intro>. This Scilab Manual and Scilab codes
written in it can be downloaded from the "Migrated Labs" section at the website
<http://scilab.in>

Contents

List of Scilab Solutions	3
1 Linear algebra: Power and Inverse Power methods for finding largest and smallest Eigenvalue and eigenvectors of matrices	5
2 Orthogonal Polynomials as Eigenfunctions of Hermitian differential operators	10
3 Determination of the principal axes of moment of inertia through diagonalization	18
4 Study of geodesics in Euclidean and other spaces(surface of a sphere, etc):Physics problem: problem of refraction.	22
5 Application to solve differential equations for a bound system – Eigen value problem	27
6 Application to computer graphics: Write operators for shear, strain, 2D rotational problems, Reflection, Translation	32
7 Lagrangian formulation in classical mechanics with constraints.	46
8 Vector-space of wave functions in Quantum-Mech: Position and Momentum differential operators and their commutator, wave function	50

List of Experiments

Solution 1.01	Power and Inverse Power Method	5
Solution 2.0	Finite Difference Method	10
Solution 3.0	Diagonalization of matrix	18
Solution 4.0	Geodesic	22
Solution 5.0	Finite Difference Method	27
Solution 6.0	Computer Graphics	32
Solution 7.0	Lagrangian Formulation	46
Solution 8.0	Hermitian Differential Op	50

List of Figures


1.1	Power and Inverse Power Method	6
2.1	Finite Difference Method	11
2.2	Finite Difference Method	16
2.3	Finite Difference Method	17
3.1	Diagonalization of matrix	21
4.1	Geodesic	23
4.2	Geodesic	23
4.3	Geodesic	24
5.1	Finite Difference Method	31
5.2	Finite Difference Method	31
6.1	Computer Graphics	33
6.2	Computer Graphics	41
6.3	Computer Graphics	42
6.4	Computer Graphics	43
6.5	Computer Graphics	44
6.6	Computer Graphics	45
7.1	Lagrangian Formulation	49
7.2	Lagrangian Formulation	49
8.1	Hermitian Differential Op	52
8.2	Hermitian Differential Op	53

Experiment: 1

Linear algebra: Power and Inverse Power methods for finding largest and smallest Eigenvalue and eigenvectors of matrices

Scilab code Solution 1.01 Power and Inverse Power Method

```
1 //Operating system: Windows 8
2 //SCILAB Ver: 5.5.2
3 //Experiment No. 1
4 //Objective: Determination of largest and smallest (
    in magnitude) Eigen value &
5 //Eigen Vectors Using Power Method and Inverse Power
    Method respectively .
6
7
8 //Enter the no dimension of a square of matrix A: 3
9 //Enter the element no (1,1):2
```



Scilab 5.5.2 Console

```
Enter the dimension of row of square matrix A: 3
Enter the element no (1,1):
2
Enter the element no (1,2):
1
Enter the element no (1,3):
1
Enter the element no (2,1):
1
Enter the element no (2,2):
2
Enter the element no (2,3):
1
Enter the element no (3,1):
1
Enter the element no (3,2):
1
Enter the element no (3,3):
5

Lowest eigen value

0.9999987

Corresponding eigen vector

- 0.7066074
0.7076057
- 0.0003643

Largest Eigen Value

5.7320494

Corresponding Eigen Vector

0.3252492
0.3252493
0.8879335

-->
```

```

10 //Enter the element no (1,2):1
11 //Enter the element no (1,3):1
12 //Enter the element no (2,1):1
13 //Enter the element no (2,2):2
14 //Enter the element no (2,3):1
15 //Enter the element no (3,1):1
16 //Enter the element no (3,2):1
17 //Enter the element no (3,3):5
18 //Let Matrix A is A=[2,1,1;1,2,1;1,1,5];
19
20 clc
21 clear
22 //
*****  

23 // Creating an input square matrix
24 //
*****  

25 m = input("Enter the dimension of row of square
matrix A: ")
26
27 for i=1:m
28     for j=1:m
29         mprintf(" Enter the element no (%d,%d): ",i,
j)
30         A(i,j)=input(" ")
31     end
32 end
33
34 //
*****  

35 // Creating initial approximation x0
36 //
*****  

37 x=rand(m,1)

```

```

38
39 // ****
40 // Finding smallest Eigen Value using Inverse Power
41 // Method
42 // ****
43 z=1
44 f=1
45 y0=rand(m,1)
46 while(f>0.00001)
47   y1=inv(A)*y0
48   lowest=norm(y1,2)
49   y0=y1/lowest
50   f=abs(z-lowest)
51   z=lowest
52 end
53 disp(lowest,'Lowest eigen value')
54 disp(y0,'Corresponding eigen vector')
55
56 // ****
57 // Finding largest Eigen Value using Power Method
58 //
59 // ****
60 x0=rand(m,1)
61 y=1
62 d=1
63 while (d>0.00001)
64   x1=A*x0
65   highest=norm(x1,2)
66   x0=x1/highest
67   d=abs(y-highest)

```


```
67      y=highest
68  end
69 disp(highest,'Largest Eigen Value')
70 disp(x0,'Corresponding Eigen Vector')
```

Experiment: 2

Orthogonal Polynomials as Eigenfunctions of Hermitian differential operators

Scilab code Solution 2.0 Finite Difference Method

```
1 // Submitted by Dr. Triranjita Srivastava. Assistant  
   Professor , Physics Dept., Kalindi College ,  
   University of Delhi  
2  
3 // Aim: To prove the orthogonality of Hermitian  
   differential Operator  
4  
5 // Two Hermitian Differential Operators ( $-id/dx$ ) and  
   ( $-d^2/dx^2$ ) are taken as an example  
6  
7 // Finite Difference Method is used to formulate the  
   matrices corresponding to the considered  
   Differential Operator  
8  
9 // This method takes the value of eigenfunction
```



The figure displays two separate SciLab 5.5.2 Console windows. Both windows show the same sequence of user input and system output, indicating the execution of a script named Experiment_02.sce.

In both windows, the user has entered the following parameters:

- Enter the first boundary, $x0 = 0$
- Enter the second boundary, $xn = 10$
- Enter number of intervals, $N = 501$
- Enter choice 1 or 2 for differential operator $-id/dx$ or $-d^2/dx^2$, respectively: 1

After these inputs, the system outputs:

The Eigenvectors of the considered Hermitian Differential Operator are Orthogonal
-->

The bottom window also shows the full path of the script file: lab(1)\experiment_02\Experiment_02.sce - SciNotes

Figure 2.1: Finite Difference Method

```

equal to 0 at the initial (x0) and final boundary
(xn), and x is defined as x=x0+i*h (h is step
size and i is integer)
10 // N is the number of interval , N should be taken as
      odd and such that step size is small enough for
      high accuracy
11
12 // Using Central Differences , tridiagonal matrix is
      obtained for (-d/dx) which has 0 as diagonal
      element and -1 as upper adjacent diagonal and 1
      as lower adjacent diagonal elements;
13
14 // Similarly , using Central Differences , tridiagonal
      matrix is obtained for (-d^2/dx^2) which has 2
      and -1 as upper and lower adjacent diagonal
      elements
15
16
17
18 clear
19 clc
20 //
*****  

21 // Boundary over which the function is to be solved
22 //
*****  

23 x0=input("Enter the first boundary , x0 = ");
24 xn=input("Enter the second boundary , xn = ");
25 N = input("Enter number of intervals , N = ");
26 h = (xn-x0)/N;      //step size
27 s=input("Enter choice 1 or 2 for differential
      operator -id/dx or -d^2/dx^2, respectively : ")
28
29 select s
30 case 1
31 //

```

```

*****
32 // Defining D1 Matrix corresponding to
33 // differential operator -id/dx
34 D1=zeros(N-1,N-1);
35
36 for i=1:(N-1)
37     x1(1,i)=x0+i*h;
38     D1(i,i)=0;
39     if i<(N-1)
40         D1(i,i+1)=-%i;
41         D1(i+1,i)=%i;
42     end
43 end
44 Final_D1=D1/2*h;
45
46 //
*****
```

47 // Finding eigenvalue and eigenvector of
48 // differential operator -id/dx
49 [eigenvector,eigenvalue] = spec(Final_D1);

50

51 case 2
52 //

53 // Defining D2 Matrix corresponding to
54 // differential operator -d^2/dx^2
55 //

```

55
56     D2=zeros(N-1,N-1);
57
58     for i=1:(N-1)
59         x1(1,i)=x0+i*h;
60         D2(i,i)=2;
61         if i<(N-1)
62             D2(i,i+1)=-1;
63             D2(i+1,i)=-1;
64         end
65     end
66     Final_D2=D2/h^2;
67
68     //
69     // Finding eigenvalue and eigenvector of
70     // differential operator -d^2/dx^2
71
72     [eigenvector,eigenvalue] = spec(Final_D2);
73
74     //
75     // Ploting of first three Eigenvector of
76     // differential operator -d^2/dx^2
77
78     x=[x0,x1,xn];
79
80     if s==1 then
81         title('3 Lowest Order Eigenvectors of -id/dx
82             ','fontsize',4);

```

```

82
83     title('3 Lowest Order Eigenvectors of -d^2/
84         dx^2', 'fontsize',4);
85
86     for k = 1:3
87         subplot(3,1,k)
88         ylabel('A (m)', 'fontsize',4)
89         a=get("current_axes");//get the handle of
90             the newly created axes
91         a.font_size=2
92         t=get("hdl") //get the handle of the newly
93             created object
94         t.font_size=2;
95         E_vector = [0;eigenvector(:,k);0];
96         plot(x,E_vector,'linewidth',2);
97     end
98         xlabel('x-coordinate (m)', 'fontsize',4)
99
100    // *****
101
102    // Orthogonality Check of eigenvector of
103        differential operator
104
105    // *****
106
107    for i=1:3
108        for j=1:3
109            P(i,j) = clean(sum((eigenvector(:,i).*%
110                conj(eigenvector(:,j))))));
111            if i~=j & P(i,j) ~=0
112                disp(" The Eigenvectors of the
113                    considered Hermitian Differential
114                    Operator are Not Orthogonal")
115                abort;
116            end
117        end
118    end

```




Figure 2.2: Finite Difference Method

109 **disp**(" The Eigenvectors of the considered
Hermitian Differential Operator are
Orthogonal")




Figure 2.3: Finite Difference Method

Experiment: 3

Determination of the principal axes of moment of inertia through diagonalization

Scilab code Solution 3.0 Diagonalization of matrix

```
1 // Submitted by Dr. Triranjita Srivastava. Assistant  
   Professor , Physics Dept., Kalindi College ,  
   University of Delhi  
2  
3 // Aim: Determination of the principal axes of  
   moment of inertia through diagonalization  
4 // Example is a Dumbbell with masses 'm1' and 'm2'  
   situated at points , say coordinates are (1,1,0)  
   and (-1,-1,0)  
5  
6 clear;  
7 clc;  
8 //  
*****  
9 //Function for Kronecker Delta  
10 //
```

```

***** ****
11 function d=delta(i,j)
12     if i==j then
13         d=1;
14     else d=0;
15     end
16 endfunction
17
18 //
***** ****
19 // Input of number of particles at discrete points
20 //
***** ****
21 n=input('enter no. of particles ')
22
23 r=zeros(3,3)
24 for i=1:n
25     mprintf("Enter the mass (in kg) at point (%d): ",i)
26     M(i)=input('')
27     mprintf("Enter the position (x,y,z) coordinate
28             at point (%d): ",i)
29     for j =1:3
30         r(i,j)=input('')
31     end
32
33 I=zeros(3,3)
34 for i=1:1:3
35     for j=1:1:3
36         for k=1:1:n
37             I(i,j)=I(i,j)+(M(k)*(sum(r(k,:).^2)*
38                         delta(i,j)-(r(k,i).*r(k,j)))))
39         end
40     end

```

```
40 end
41 disp("Moment of Inertia Tensor for given problem is:
      ")
42 disp(I)
43 [ab,x,bs]=bdiag(I);
44 disp("Moment of Inertia Tensor after diagonalization
      is:    ")
45 disp(ab)
```

The image shows a screenshot of the Scilab 5.5.2 Console window. The window title is "Scilab 5.5.2 Console". The menu bar includes "File", "Edit", "Control", "Applications", and "?". Below the menu is a toolbar with various icons. The main console area displays the following text:

```
enter no. of particles 2
Enter the mass (in kg) at point (1):
0.5
Enter the position (x,y,z) coordinate at point (1):
1
1
0
Enter the mass (in kg) at point (2):
0.5
Enter the position (x,y,z) coordinate at point (2):
-1
-1
0

Moment of Inertia Tensor for given problem is:

 1. - 1.   0.
 - 1.   1.   0.
 0.   0.   2.

Moment of Inertia Tensor after diagonalization is:

 2.   0.   0.
 0.   0.   0.
 0.   0.   2.

-->
```


Figure 3.1: Diagonalization of matrix

Experiment: 4

**Study of geodesics in Euclidean
and other spaces(surface of a
sphere, etc):Physics problem:
problem of refraction.**

Scilab code Solution 4.0 Geodesic

```
1 // Submitted by Dr. Triranjita Srivastava. Assistant
   Professor , Physics Dept., Kalindi College ,
   University of Delhi
2
3 // Aim: To study geodesics in Euclidean and
   Cylindrical Polar coordinate System
4
5 clc;
6 clear;
```



The image shows a screenshot of the Scilab 5.5.2 Console window. The title bar reads "Scilab 5.5.2 Console". The main area contains the following text:

```
Input x coordinate of point A 1
Input y coordinate of point A 1
Input x coordinate of point B 6
Input y coordinate of point B 7
Input angular coordinate (in degree) of point A 10
Input z coordinate of point A 2
Input angular coordinate (in degree) of point B 340
Input z coordinate of point B 18
-->
```

Figure 4.1: Geodesic




Figure 4.2: Geodesic




Figure 4.3: Geodesic

```

7 // ****
8 // ***Equation of Geodesic (straight line) passing
9 // through two points in Euclidean Geometry
10 x1=input ("Input x coordinate of point A ")
11 y1=input ("Input y coordinate of point A ")
12 x2=input ("Input x coordinate of point B ")
13 y2=input ("Input y coordinate of point B ")
14 x=[0 ,0.1 ,10]
15 m=(y2-y1)/(x2-x1);
16 y=y1+m*(x-x1);
17 scf()
18 xlabel('x-coordinates ', 'fontsize ',5)
19 ylabel('y-coordinates ', 'fontsize ',5)
20 title('Geodesic in Euclidean Geometry ', 'fontsize ',5)
21 a=get("current_axes")           //get the handle of the
22 a.font_size=4
23 t=get("hdl")                  //get the handle of the

```

```

            newly created object
24 t.font_size=5
25 plot(x,y,'linewidth',3)
26 //
    //*****=====
27 //// Plotting of cylinder
28 //
    //*****=====

29 a=5;
30 theta=linspace(0,2*pi,30)
31 z=linspace(0,30,30)
32 [theta,z]=meshgrid(theta,z)
33 x=a*cos(theta);
34 y=a*sin(theta);
35 scf()
36 surf(x,y,z,'facecolor','green','edge','white')
37
38 //
    *****=====

39 //Equation of Geodesic ( helix) in cylindrical
    Coordinate System
40 //
    *****=====

41 theta1=input("Input angular coordinate (in degree)
    of point A")
42 z1=input("Input z coordinate of point A")
43 theta2=input("Input angular coordinate (in degree)
    of point B")
44 z2=input("Input z coordinate of point B")
45 t1=theta1*pi/180;
46 t2=theta2*pi/180;
47 t=linspace(t1,t2,100)
48 z=z1+(z2-z1)*(t-t1)/(t2-t1);
49 title('Geodesic in Cylindrical Polar Coordinate

```

```
    System', 'fontsize',5)  
50 param3d(a*cos(t), a*sin(t),z)
```

Experiment: 5

Application to solve differential equations for a bound system – Eigen value problem

Scilab code Solution 5.0 Finite Difference Method

```
1 // Submitted by Dr. Triranjita Srivastava. Assistant  
   Professor , Physics Dept., Kalindi College ,  
   University of Delhi  
2 //Operating system: Windows  
3 //SCILAB Ver: 5.5.2  
4  
5 //Objective: Application to solve differential  
   equations for a bound system – Eigenvalue Problem  
6  
7 // Example:Let us find out the energy eigenvalues  
   and corresponding wavefunction of a particle of  
   mass 'M' trapped in infinite potential Well (  
   potential V=0) of width 'L'  
8 //We implement Finite Difference Method (FDM) to  
   obtain the eigenvalues  
9 // By using FDM the second order differential  
   operator is replaced by a trigonal matrix and
```

```

          the problem reduces to a simple eigenvalue
          problem

10
11
12 clc
13 clear
14 h_cut=1.05457*10^-34           // (Plancks
           constant/2 pi) J-s
15 L=input("Enter the width of the potential well L (in
           m) = ")
16 M=input("Enter mass of particle M (in kg) = ")
17 n=250                          // Number of
           divisions for FDM
18 N=(2*n)+1
19 x1=0                           // Initial value
           of x-coordinate
20 s=(L-x1)/N                     // Step size for
           implementing FDM
21 EV=6.242*10^18                 // joule to eV
           conversion
22 //
***** *****
23 // Hamiltonian Matrix H=T+V;   T=Kinetic energy
           operator (-d^2/dx^2)*h_cut^2/2M;      V= 0 (for
           infinite potential well)
24 //
***** *****

25 T=zeros(N-1,N-1)
26 for i=1:(N-1)
27     x1=x1+s
28     T(i,i)=2
29     if (i<(N-1))
30         T(i,i+1)=-1
31         T(i+1,i)=-1
32 end
33 end

```

```

34
35 H=(T*h_cut^2*EV/(2*M*s^2)) // Hamiltonian Matrix
36
37 // ****
38 // Finding eigenvalues and corresponding
39 // wavefunctions
40 // ****
41 eigenvalues=spec(H)
42 disp("The eigenvalues (eV) of three lowest states
        obtained by FDM are ")
43 disp(eigenvalues(1:3))
44 [U,z]=spec(H)
45 // ****
46 // Plotting of three lowest order wavefunctions
47 // ****
48 x=linspace(s,L,N-1) // creating
    x-coordinates for potential well
49 xlabel('x-coordinate (10^-10 m)', 'fontsize',5)
50 ylabel('Wavefunction (a.u.)', 'fontsize',5)
51 title('Graph of Wavefunction for three lowest order
        mode', 'fontsize',5)
52 a=get("current_axes") //get the handle of the
    newly created axes
53 a.font_size=2
54 t=get("hdl") //get the handle of the
    newly created object
55 t.font_size=5
56 plot(x*10^-10,U(:,1) ./ max(U(:,1))), 'r', 'linewidth',3)

```

```

57 plot(x*10^10,U(:,2) ./ max(U(:,2)), 'b', 'linewidth', 3)
58 plot(x*10^10,U(:,3) ./ max(U(:,3)), 'g', 'linewidth', 3)
59 h1=legend(['Ground State'; 'I Excited State'; 'II
    Excited State'],5)
60 h1.font_size=2
61
62 // ****
63 // Comparison of obtained eigenvalues with
       analytical solution
64 //
*****
```

65 disp("The eigenvalues (eV) of three lowest states
 obtained by analytical results are ")
66 for j=1:3
67 E(j)=j^2*pi^2*h_cut^2*EV/(2*M*L^2)
68 disp (E(j))
69 end

Scilab 5.5.2 Console

File Edit Control Applications ?

Enter the width of the potential well L (in m) = 2×10^{-10}
 Enter mass of particle M (in kg) = 9.1×10^{-31}

The eigenvalues (eV) of three lowest states obtained by FDM are

```
9.4111248
37.644129
84.697903
```

The eigenvalues (eV) of three lowest states obtained by analytical results are

```
9.4111556
37.644623
84.700401
```

-->|

Figure 5.1: Finite Difference Method




Figure 5.2: Finite Difference Method

Experiment: 6

Application to computer graphics: Write operators for shear, strain, 2D rotational problems, Reflection, Translation

Scilab code Solution 6.0 Computer Graphics

```
1 // Submitted by Dr. Triranjita Srivastava. Assistant  
   Professor , Physics Dept., Kalindi College ,  
   University of Delhi  
2  
3 //Operating system: Windows 8  
4 //SCILAB Ver: 5.5.2  
5  
6 // Objective: To study computer graphics.  
7 // One can create any object of choice and implement  
   various tranformations , like , Shear , Strain , 2D  
   rotation , Reflection , Translation ,
```




Figure 6.1: Computer Graphics

```

8
9 clc
10 clear
11 // ****
12 //Creation of an object (say , rectangle)
13 //
14 x=[0,5,5,0,0]
15 y=[0,0,3,3,0]
16 N=[x;y]
17 //
18 // ****
19 //To Study Shear
20 //
21 // ****

```

```

21 l=input("Enter 1, 2 or 3 for shear along x- axis , y-
           axis or both axis , respectively : ")
22
23 figure(1)
24 xlabel('x-coordinates (cm)', 'fontsize',5)
25 ylabel('y-coordinates (cm)', 'fontsize',5)
26 a=get("current_axes")           // get the handle of the
           newly created axes
27 a.font_size=4
28 t=get("hdl")                   // get the handle of the
           newly created object
29 t.font_size=5
30
31 select 1
32   case 1
33     // Transformation Matrix for Shear parallel
        to x-axis
34     s=input("Enter the value of shear s = ")
35     Sx=[1 s; 0 1]
36     S=Sx*N
37     title('Shear parallel to x-axis', 'fontsize',
           ,5)
38     a.data_bounds=[0,0;8,5]
39   case 2
40     // Transformation Matrix for Shear parallel
        to y-axis
41     s=input("Enter the value of shear s = ")
42     Sy=[1 0; s 1]
43     S=Sy*N
44     title('Shear parallel to y-axis', 'fontsize',
           ,5)
45     a.data_bounds=[0,0;6,8]
46   case 3
47     // Transformation Matrix for Shear in x and
        y-direction
48     sx=input("Enter the value of shear in x-
           direction sx = ")
49     sy=input("Enter the value of shear in y-

```

```

                direction sy = " )
50      Sxy=[1 sx; sy 1]
51      S=Sxy*N
52      title('Shear in x and y direction ', 'fontsize
53      ',5)
53      a.data_bounds=[0 ,0 ;6 ,8]
54  end
55  plot(x,y,'linewidth ',3)
56  plot(S(1,: ),S(2,: ),'—r','linewidth ',3)
57 h1=legend(['old coordinates ';'new coordinates '])
58 h1.font_size=3
59
60
61 // ****
62 //To Study Strain
63 //
64 ****
65 p=input("Enter 1 or 2 for strain along x- axis or y-
66 axis , respectively : ")
67 figure(2)
68 xlabel('x-coordinates (cm)', 'fontsize ',5)
69 ylabel('y-coordinates (cm)', 'fontsize ',5)
70 a=get("current_axes"); //get the handle of the
71     newly created axes
71 a.font_size=4
72 t=get("hdl") //get the handle of the newly created
73     object
73 t.font_size=5;
74
75 select p
76     case 1
77 // Transformation Matrix for Strain along x-
78     axis

```

```

78     stx=input("Enter the value of strain stx = "
79             )
80     Str_x=[stx 0; 0 1]
81     ST=Str_x*N;
82     title('Strain along x-axis ', 'fontsize ',5);
83     a.data_bounds=[0,0;8,5];
84 //      Transformation Matrix for strain along y-
85     axis
86     sty=input("Enter the value of strain sty = "
87             )
88     Str_y=[1 0; 0 sty]
89     ST=Str_y*N;
90     title('Strain along y-axis ', 'fontsize ',5);
91     a.data_bounds=[0,0;6,8];
92 end
93 plot(x,y, 'linewidth ',3);
94 plot(ST(1,:),ST(2,:),'r','linewidth ',3)
95 h1=legend(['old coordinates';'new coordinates']);
96 h1.font_size=3
97
98 // ****
99 //To Study 2D Rotation
100 //
101 ****
102 k=input("Enter 1 or 2 for 2D Rotation in clockwise
103 and anticlockwise direction, respectively: ")
104 th=input("Enter the required angle for rotation th (
105 in degree) = ")
106 figure(3)
107 xlabel('x-coordinates (cm)', 'fontsize ',5)
108 ylabel('y-coordinates (cm)', 'fontsize ',5)

```

```

107 a=get("current_axes");//get the handle of the newly
    created axes
108 a.font_size=4
109 t=get("hdl") //get the handle of the newly created
    object
110 t.font_size=5;
111
112 select k
113     case 1
114         // Transformation Matrix for Rotation in
            clockwise direction
115         C1=[cosd(th),sind(th);-sind(th),cosd(th)]
116         Rot=C1*N;
117         title('Rotation in clockwise direction','
            fontsize',5);
118         a.data_bounds=[0,0;8,5];
119     case 2
120         // Transformation Matrix for Rotation in
            anticlockwise direction
121         Anti=[cosd(th),-sind(th);sind(th),cosd(th)]
122         Rot=Anti*N;
123         title('Rotation in anticlockwise direction','
            fontsize',5);
124         a.data_bounds=[0,0;6,8];
125 end
126 plot(x,y,'linewidth',3);
127 plot(Rot(1,: ),Rot(2,: ),'—r','linewidth',3)
128 hl=legend(['old coordinates';'new coordinates']);
129 hl.font_size=3
130
131 // ****
132 //To Study the reflection
133 //
134 *****

132 //To Study the reflection
133 //
134 *****

134 j=input("Enter 1, 2 or 3 for reflection about x-

```

```

axis , y-axis or origin , respectively : ")
135
136 figure(4)
137 xlabel('x-coordinates (cm)', 'fontsize',5)
138 ylabel('y-coordinates (cm)', 'fontsize',5)
139
140 a=get("current_axes"); //get the handle of the newly
    created axes
141 a.font_size=4
142 t=get("hdl") //get the handle of the newly created
    object
143 t.font_size=5;
144 select j
145 case 1
146     // Transformation Matrix for Reflection about x-
        axis
147     Rx=[1 0; 0 -1]
148     R=Rx*N;
149     title('Reflection about x-axis', 'fontsize',
            ,5);
150     a.data_bounds=[0,-4;6,4];
151 case 2
152     // Transformation Matrix for Reflection about y-
        axis
153     Ry=[-1 0; 0 1]
154     R=Ry*N;
155     title('Reflection about y-axis', 'fontsize',
            ,5);
156     a.data_bounds=[0,0;8,4];
157 case 3
158     // Transformation Matrix for Reflection about
        origin
159     Rxy=[-1 0; 0 -1]
160     R=Rxy*N;
161     title('Reflection about origin', 'fontsize',
            ,5);
162     a.data_bounds=[-8,-5;8,5];
163 end

```

```

164
165 plot(x,y,'linewidth',3);
166 plot(R(1,:),R(2,:),'—r','linewidth',3)
167 h1=legend(['old coordinates';'new coordinates']);
168 h1.font_size=5
169
170 //*****
171 //To Study translation
172 //*****
173 i=input("Enter 1, 2 or 3 for translation along x-
axis , y-axis or both directions , respectively : ")
174
175 figure(5)
176 xlabel('x-coordinates (cm)', 'fontsize',5)
177 ylabel('y-coordinates (cm)', 'fontsize',5)
178 a=get("current_axes"); //get the handle of the
    newly created axes
179 a.font_size=4
180 t=get("hdl") //get the handle of the newly created
    object
181 t.font_size=5;
182
183 select i
184     case 1
185         // Transformation Matrix for translation
            along to x-axis
186         tx=input("Enter the required translation
            along x direction tx = ")
187         T1=[ones(1,length(x));zeros(1,length(x))];
188         X=N+tx*T1;
189         title('Translation along to x-axis ','
            fontsize',5);
190         a.data_bounds=[0,0;8,5];
191     case 2

```

```

192      // Transformation Matrix for translation
193      // along to y-axis
194      ty=input("Enter the required translation
195      along x direction ty = ")
196      T1=[zeros(1,length(x));ones(1,length(x))];
197      X=N+ty*T1;
198      title('Translation along to y-axis ','
199      fontsize',5);
200      a.data_bounds=[0,0;6,8];
201      case 3
202      // Transformation Matrix for translation
203      // along to y-axis
204      tx=input("Enter the required translation
205      along x direction tx = ")
206      ty=input("Enter the required translation
207      along y direction ty = ")
208      T1=[ones(1,length(x));zeros(1,length(x))];
209      T2=[zeros(1,length(x));ones(1,length(x))];
210      X=N+tx*T1+ty*T2;
211      title('Translation along to y-axis ','
212      fontsize',5);
213      a.data_bounds=[0,0;6,8];
214  end
215  plot(x,y,'linewidth',3);
216  plot(X(1,:),X(2,:),'—r','linewidth',3)
217  h1=legend(['old coordinates';'new coordinates']);
218  h1.font_size=3

```




Figure 6.2: Computer Graphics




Figure 6.3: Computer Graphics




Figure 6.4: Computer Graphics




Figure 6.5: Computer Graphics




Figure 6.6: Computer Graphics

Experiment: 7

Lagrangian formulation in classical mechanics with constraints.

Scilab code Solution 7.0 Lagrangian Formulation

```
1 // Submitted by Dr. Triranjita Srivastava. Assistant Professor , Physics Dept., Kalindi College , University of Delhi
2
3 //Operating system: Windows 8
4 //SCILAB Ver: 5.5.2
5 //Objectiv: Lagrangian formulation in classical mechanics with constraints
6 //Example: Simple Pendulum of length L (m)operating in gravitational field . After applying Lagrangian formulation this problem reduces to a simple second order differential equation [(d^2 theta/dt^2)+(g/L) sin(theta)]=0. Here theta is angular displacement .
7 // We implemented ordinary differential equation ( ODE) Solver to solve the second order differential equation
```

```

8 //We present plot of solution of angular
    displacement for t=0 to t=10 seconds
9
10 clear
11 clc
12 L=input('Enter the length of pendulum (m) L = ')
13 g = 9.8                                // acceleration due to
    gravity (m/s^2)
14 k=g/L
15 theta=input('Enter the initial angular displacement
    (radian) at (t = 0) = ') ;           // Initial
    angular displacement at t = 0
16 dt=input('Enter initial d_theta/dt (radian) at (t =
    0) = ') ;                         // Initial boundary condition
    d_theta/dt at t = 0
17 //
    //***** Function declaration for ODE
18 ///
19 //
    //***** Function declaration for ODE
20 t=linspace(0,10,200)
21 function dx=f(t,x,k)
22     dx(1)=x(2)
23     dx(2)=-k*sin(x(1))
24 endfunction
25 //
    //***** Solving second order differential equation by
    ODE solver
26 ///
    //***** Solving second order differential equation by
    ODE solver
27 //
    //***** Solving second order differential equation by
    ODE solver
28 y=ode([theta;dt],0,t,f)
29 ysol=y(1,:)
30 ydotsol = y(2,:)

```

```

31
32 // ****
33 //// Plotting the solution (angular displacement (
34 // theta) and d_theta/dt)
35 scf()
36 title('Solution of Simple Pendulum', 'fontsize',5)
37 ylabel('Solution —>', 'fontsize',5)
38 xlabel('t (sec) —> ', 'fontsize',5)
39 a=get("current_axes")           //get the handle of the
                                  newly created axes
40 a.font_size=4
41 t=get("hdl")                  //get the handle of the
                                  newly created object
42 t.font_size=5
43 plot(t,ysol,'r','linewidth',3)
44 plot(t,ydotsol,'k','linewidth',3)
45 h1 = legend(['$\theta$'; '$d\theta/dt$'])
46 h1.font_size=3

```

The image shows a Scilab 5.5.2 Console window. The title bar says "Scilab 5.5.2 Console". The main area contains the following text:

```
Enter the length of pendulum (m) L = 1
Enter the initial angular displacement (radian) at (t = 0) = %pi/10
Enter initial d_theta/dt (radian) at (t = 0) = 0
-->
```

Figure 7.1: Lagrangian Formulation




Figure 7.2: Lagrangian Formulation

Experiment: 8

Vector-space of wave functions in Quantum-Mech: Position and Momentum differential operators and their commutator, wave function

Scilab code Solution 8.0 Hermitian Differential Op

```
1 // Submitted by Dr. Triranjita Srivastava. Assistant
   Professor , Physics Dept., Kalindi College ,
   University of Delhi
2
3 // Aim: To show the commutator relation in postion
   and momentum space  $[x, p] = i\hbar \text{cut}$  or n general  $[x^n, p] = i\hbar \text{cut} * n * x^{(n-1)}$ 
4 // Two examples are shown in this program
5 // 1. Let the first function is fx=x
6 // 2. Let the second function is fx=x^3
7 // For simplicity let the wavefunction A=x
8 //  $[fx, p] = (i\hbar \text{cut}) (dfx/dx)$ 
9 // h_cut=h/2pi; h is planck constant
```

```

10
11
12 clc
13 x=poly(0,"x")
14 h_cut=1.05*(10)^-34 // h_cut=h/2 pi ,
    units is in Joule-sec
15 A=x // Considered
    Wavefunction is A=x
16
17 s=input("Enter 1 or 2 to choose the function as fx =
    x or fx = x^3, s= ")
18 select s
19 case 1
20     fx=x // First
        wavefunction
21 case 2
22     fx=x^3 // Second wavefunction
23 end
24
25 fx_p=fx*(-%i*h_cut)*derivat(A)
26 p_fx=(-%i*h_cut)*derivat(fx*A)
27 commutator=(fx_p-p_fx)
28 disp("[ fx , p ] = ")
29 disp(commutator)
30 disp ("The result contains an extra x because the
    chosen wavefunction is A = x")

```


The image shows a screenshot of the Scilab 5.5.2 Console window. The window title is "Scilab 5.5.2 Console". The console output is as follows:

```
Enter 1 or 2 to choose the function as fx = x or fx = x^3, s= 1
[fx,p] =
Real part

0
Imaginary part

1.050D-34x
The result contains an extra x because the chosen wavefunction is A = x
-->|
```

Figure 8.1: Hermitian Differential Op



Scilab 5.5.2 Console

```
Enter 1 or 2 to choose the function as fx = x or fx = x^3, s= 2
[fx,p] =
Real part

0
Imaginary part

      3
3.150D-34x
The result contains an extra x because the chosen wavefunction is A = x
-->|
```

Figure 8.2: Hermitian Differential Op